

Ceiling, Suspensions and Wall

BEBOP



TARGETTI

BEBOP

Ceiling / Suspension

GENERAL INFO

LED pendant and ceiling mounted for direct diffuse lighting.
Ø90mm

LED

Chip on board
From 1545lm to 1750lm
3000K – 4000K
Ra80 - Ra90

PRODUCT EFFICACY

Up to 91lm/W

OPTICS

MWFL - WFL

POWER SUPPLY

Electronic

MATERIAL

Painted aluminium body.
Painted polycarbonate front element. Die-cast aluminium finned internal heat sink.

ON DEMAND



Easy Custom Colour



DALI



2700K-3500K

A range of high performance products characterised by simple, soft and rounded lines. Available in three different versions for ceiling mounted, suspension and recessed installation.

Also available in a recessed installation version.

In all versions the LED lamps are retracted and hidden from view to ensure optimum visual comfort. The flexible installation makes it possible to use the same type of light in environments with different architectural characteristics.




Indoor

BEBOP



Ceiling



LED / 12W / MWFL

	3000K	H(m)	D(m)	E _{max} (lx)
Ra80			48°	
Fixture Power	14W	1	0.90	1823
Source Flux	1706lm	2	1.79	456
Fixture Flux	1310lm	3	2.69	203
Efficacy	95lm/W	4	3.59	114
TS901	I _{max} =1079cd/klm	I _{max}	1840cd	5 4.48 73

Driver	Colour	3000K	4000K
EL.	○	1T4768EL	1T4769EL
EL.	●	1T5414EL	1T5415EL

LED / 12W / WFL

	3000K	H(m)	D(m)	E _{max} (lx)
Ra80			64°	
Fixture Power	14W	1	1.24	1087
Source Flux	1706lm	2	2.49	272
Fixture Flux	1285lm	3	3.73	121
Efficacy	93lm/W	4	4.98	68
TS900	I _{max} =688cd/klm	I _{max}	1174cd	5 6.22 43


Driver	Colour	3000K	4000K
EL.	○	1T4766EL	1T4767EL
EL.	●	1T5416EL	1T5417EL

Note

Ra90: to order this version it is necessary to add the suffix "90" at the end of the standard code (Ra80).



Suspension



LED / 12W / MWFL

	3000K	H(m)	D(m)	E _{max} (lx)
Ra80			48°	
Fixture Power	14W	1	0.90	1823
Source Flux	1706lm	2	1.79	456
Fixture Flux	1310lm	3	2.69	203
Efficacy	95lm/W	4	3.59	114
TS901	I _{max} =1079cd/klm	I _{max}	1840cd	5 4.48 73

Driver	Colour	3000K	4000K
EL.	○	1T4764EL	1T4765EL
EL.	●	1T5418EL	1T5419EL

LED / 12W / WFL

	3000K	H(m)	D(m)	E _{max} (lx)
Ra80			64°	
Fixture Power	14W	1	1.24	1087
Source Flux	1706lm	2	2.49	272
Fixture Flux	1285lm	3	3.73	121
Efficacy	93lm/W	4	4.98	68
TS900	I _{max} =688cd/klm	I _{max}	1174cd	5 6.22 43

Driver	Colour	3000K	4000K
EL.	○	1T4762EL	1T4763EL
EL.	●	1T5420EL	1T5421EL

Note

Complete with 2000mm long steel suspension cable with micrometric adjustment system.

Ra90: to order this version it is necessary to add the suffix "90" at the end of the standard code (Ra80).

Requisites and information

All fixtures of the Targetti collection have been designed and produced to comply with European Standard EN60598-1 relative to the safety requisite of light fixtures.



All fixtures comply with the following directives:

- EMC Directive 2014/30/EU
- LV Directive 2014/35/EU
- RoHS Directive 2011/65/EU

Unless specified otherwise

- all fixtures are supplied without lamps;
- all fixtures are sold separately;
- all measurements are expressed in millimeters;
- all fixtures at low voltage are supplied without transformer;
- For products in Class III performance is only guaranteed using the electronic power supplies and drivers indicated in the catalogue.

Consorzio ecolight

Targetti Sankey Spa is a member of the Ecolight consortium that was set up in 2004 (D.Lgs. 49/2014) to comply with the provisions of the European Directive that was adopted in Italy as the European Directive 2012/19/EU for WEEE on managing, recovering and treating waste electrical and electronic equipment, used batteries and accumulators in compliance with all applicable legislation.

The colors of the products illustrated are reproduced as faithfully as possible compatibly with the technical limitations of the printed medium. The company reserves the right to make changes to the production without notice. Reproduction of this catalogue or any part of it is prohibited. The products illustrated in this catalogue are covered by one or more Italian or international patents. The company will take legal action against any imitators.



TARGETTI SANKEY SpA

Certificated ISO 9001 n° 9130. TAR1
Certificated ISO 14001 n° IT319206

The Enec mark, ISO9001 and ISO14001 certifications and the CE marking all guarantee that the activities carried out internally in the company are governed and controlled by procedures which assure constant level of quality.

Accredited laboratory in accordance with ISO 17025.

Light beam apertures

from	to	beam	
5°	10°	Narrow Spot	NSP
11°	25°	Spot	SP
26°	40°	Flood	FL
41°	50°	Medium Wide Flood	MWFL
51°	70°	Wide Flood	WFL
71°	120°	Very Wide Flood	VWFL
		Wall Washer	WW
		Narrow Asymmetric	N. ASYM
		Asymmetric	ASYM

Icons legend

	Class I luminaire in which the protection against electrical shock is guaranteed by the connections of the conductive elements accessible to a protective conductor (earth connection).
	Luminaire in which the connection to a protective conductor (earth connection) guarantees the immunity to radio noises.
	Class II luminaire (double insulation), protected against the accidental contact with parts under tension from the user.
	Class III luminaire, suitable for connection to very low voltage circuits.
	Solid particle and liquid ingress protection degree.
	Protection degree - Recessed part . Protection degree - Exposed part.
	Impact protection degree.
	ENEC European Norms Electrical Certification.

Particular symbols

	Weight of the single fixture.
	Cable length.
	Walk-over.
	Driver-over safe.
	Fixtures that have parameters below the minimum visibility threshold $PstLM \leq 1$ and $SVM \leq 0.4$ (IEC TR 61547-1 and IEC TR 63158).
DBS	Dynamic Beam Shaper optical technology with remote management of the beam opening.
	LED with $Ra_{\text{---}}$ where not present in the catalogue, available on request.
	Different colour temperatures available on request.
	Custom finish of your choice from the Targetti Colours range and RAL indicated in the colour chart can be downloaded on line from the download section.
	Treatment carried out on request.
	Supplied on request with an integrated or remote 110-277Vac power supply as indicated for the standard model.
	LED version with a different "Tunable White" tone available on request.

Note

- ➔ Please contact us for on demand treatments and versions.
- ➔ The performances reported on the products refer to the use of the recommended drivers.
- ➔ The drivers selected by Targetti make the fixtures "Safe Flicker".

